

RG-S5750-S





Contents

1

Ruijie# write

Building configuration...

Write to boot config file: [/config.text]



Contents

Ctrl Version: RGOS 10.4(3b16) Release(146430)
MTD_DRIVER-5-MTD_NAND_FOUND: 1 NAND chips(chip size : 134217728) detected
1 nand chip(s) found on the target.
Press Ctrl+C to enter Ctrl ...

// log 3s ctrl+c CTRL

Hot Commands:

Ctrl>^C

Ctrl>^C

Ctrl>rename confi g. text confi g. bak

Ctrl>load //

Ruijie#copy flash: confi g. bak flash: confi g. text

Ruijie#copy



Contents



www.ruijie.com.cn


RGOS

Ruijie#copy





Contents



```
Ruijie#show tempr
```

```
Device-1:  
Current Tempr: 29.0 C
```

		指示灯灭	端口未 Link	
1000M Link Up				绿色常亮 端口 1
1000M 数据收发	1000Mbps RJ-45 接口指示			绿色闪烁 端口 1
100/10M Link Up				黄灯常亮 端口
100/10M 数据收发				黄灯闪烁 端口

```
Ruijie#show fans
```

```
Device-1:
```

Item	Status	Serial Number	Ver	Speed
1	Normal	-	1	//normal
2	Normal	-	1	



CPU • i V i - Ü ä ½ Â K 3 °) T ¿ ! € \$ ñ † A ' 0 L



Ruijie#show interfaces counters

```
Interface : Gi gabi tEthernet 0/1
5 minutes input rate : 1034 bits/sec, 1 packets/sec
5 minutes output rate : 65 bits/sec, 0 packets/sec
InOctets          : 8918550
InUcastPkts      : 4
InMul ti castPkts : 103298
InBroadcastPkts  : 0
OutOctets         : 524352
OutUcastPkts     : 4
OutMul ti castPkts : 2298
OutBroadcastPkts : 0
Undersize packets : 0
Oversize packets : 0
collisions       : 0
Fragments       : 0
Jabbers         : 0
CRC alignment errors : 0
AlignmentErrors  : 0
FCSErrors       : 0
dropped packet events (due to lack of resources): 0
packets received of length (in octets):
```





Contents





















